

nEXT TURBOMOLECULAR PUMPING STATION

edwardsvacuum.com

nEXT turbomolecular pumping stations are configurable with turbomolecular pump speeds ranging from 47 to 400 ls⁻¹ and a choice of oil sealed or dry backing pumps ranging from 1 to 20 m³h⁻¹. All our nEXT turbomolecular pumping stations feature an integrated TIC turbo and instrument controller offering full control of the package via a simple intuitive interface.

The nEXT turbomolecular pumping stations are supplied fully assembled and ready to run straight out of the box and include common accessories such as mist filters and mains cables as appropriate to the chosen pumps. As fully featured high end stations they include RS232 serial communications and Windows® software for monitoring and control.



Features and benefits

Range of turbomolecular pump options

Choice of turbomolecular pump with speeds ranging from 47 to 400 ls⁻¹ and inlet flanges from DN40 to DN160.

Fully controllable

TIC turbo and instrument controller offers full control of pumps and up to 3 Active gauges as well as offering full serial remote communications.

Vent valve option

Optional turbomolecular pump vent valve can be ordered as part of cart assembly.

User serviceable

All nEXT turbomolecular pumps and backing pumps are fully user serviceable.

Robust metal frame

All metal frame with locking castors for a robust but easily mobile system. Bench mounting kit included for safe bench top operation.

Choice of backing pumps

Choice of oil sealed and dry backing pumps with capacities ranging from 1 to 20 m³h⁻¹.

Low vibration

Backing pump mounted on anti-vibration mounts for low levels of transmitted vibration.

'Plug and play' turbomolecular pumping station

Everything about our range of nEXT turbomolecular pumping stations has been developed to provide a comprehensive vacuum solution with the latest technological advances for easy installation and operation.

A simplified ordering matrix and expanded range, to include turbopumps with speeds from 42 ls^{-1} to 400 ls^{-1} , enables you to select the most appropriate combination for your application, fully assembled and ready to go.

1. Choose your turbopump



nEXT85 (84 ls^{-1})
¹⁾



nEXT240 (240 ls^{-1})
¹⁾



nEXT300 (300 ls^{-1})
¹⁾



nEXT400 (400 ls^{-1})
¹⁾

2. Choose your backing pump



E2M1.5 ($1.6 \text{ m}^3\text{h}^{-1}$)



RV5 ($5.1 \text{ m}^3\text{h}^{-1}$)



RV12 ($12.0 \text{ m}^3\text{h}^{-1}$)



XDD1 ($1.2 \text{ m}^3\text{h}^{-1}$)



nXDS

nXDS6i ($6.2 \text{ m}^3\text{h}^{-1}$)

nXDS10i ($11.4 \text{ m}^3\text{h}^{-1}$)

nXDS15i ($15.1 \text{ m}^3\text{h}^{-1}$)

nXDS20i ($22.0 \text{ m}^3\text{h}^{-1}$)

3. Select your voltage



Ordering information

nEXT turbomolecular pumping station:

T S - - 0 0

Turbomolecular pump

B nEXT240

C nEXT300

D nEXT400

E nEXT240T

F nEXT300T

G nEXT400T

J nEXT85D

K nEXT85H

Inlet Flange

1 DN40NW (nEXT85)

2 DN63ISO-K (nEXT85)

3 DN63CF (nEXT85)

4 DN100ISO-K (nEXT240/300)

5 DN100CF (nEXT240/300)

6 DN160ISO-K (nEXT400)

7 DN160CF (nEXT400)

Backing Pump

1 E2M1.5

2 RV5

3 RV12

A XDD1

D nXDS6i

E nXDS10i

F nXDS15i

G nXDS20i

Vent Option

0 Manual Vent

1 TAV5 Vent Valve

Electrical Supply


1 220-240 V 50/60 Hz (Europe)

2 110-120 V 50/60 Hz (USA)

3 200 V 50/60 Hz (Japan)

4 220-240 V 50/60 Hz (UK)

Official Distributor in



EZZI VISION

Vacuum and Thin Film Technology

CONTACT US

T: 1800 GO EZZI
E: sales@ezzivision.com.au
W: ezzivision.com.au

VIC: 13/62 Ramset Drive, Chirnside Park,
VIC 3116, Australia

NSW: Unit 1, 80 O'Riordan St, Alexandria,
NSW 2015, Australia

WA: Unit 11, 24 Baile Road, Canning Vale,
WA 6155 Australia

‡ For Japan low volts on E2M1.5 please order the USA voltage variant, for all other pumps please order Japan version and specify low volts on your order

